

## CLAIMS

1. A laminated material characterized in that, in the laminated material wherein a polyolefinic thermoplastic elastomer(B) containing an oily softening agent is laminated on the surface layer comprising a polyolefinic thermoplastic elastomer(A) containing an oily softening agent, the ratio(a) of the oily softening agent to the amorphous component(or to the total of the amorphous component and polyethylene if polyethylene is incorporated) in said thermoplastic elastomer(A) and the ratio(b) of the oily softening agent to the amorphous component(or to the total of the amorphous component and polyethylene if polyethylene is incorporated) in said thermoplastic elastomer(B) satisfy the following requisites;

`ratio(a) ≈ ratio(b)`,

ratio(a) = 5 to 200 wt.%, and

ratio(b) = 5 to 200 wt. %.

2. A laminated material characterized in that, in the laminated material according to Claim 1, the polyolefinic thermoplastic elastomer (A) and/or the polyolefinic thermoplastic elastomer (B) contain(s) polyethylene and in addition the ratio (a') of the oily softening agent to the amorphous component in said thermoplastic elastomer (A) and the ratio (b') of the oily softening agent to the amorphous component in said thermoplastic elastomer (B) satisfy the following requisites;

$$\text{ratio}(a') \geq 0.8 \times \text{ratio}(b'),$$

ratio(a') = 5 to 200 wt.%, and

Sub  
A1  
cont  
Sub A

~~ratio(b') = 5 to 200 wt.%.~~

3. A glass-run channel comprising the laminated material according to Claim 1.
4. A glass-run channel comprising the laminated material according to Claim 2.
5. A roof molding, side molding or window molding for automobiles comprising the laminated material according to Claim 1.
6. A roof molding, side molding or window molding for automobiles comprising the laminated material according to Claim 2.

DRAFTED = EDITED = PROOFED = CHECKED